
Documentation for EXT:solrfluidgrouping
grouping for EXT:solr
Release 1.0.0

Timo Hund

2018-02-23 16:43

CONTENTS

1	What does it do?	1
2	Configuration Reference	3
2.1	tx_solr.search.grouping	4
2.1.1	grouping.numberOfGroups	4
2.1.2	grouping.numberOfResultsPerGroup	4
2.1.3	grouping.allowGetParameterSwitch	4
2.1.4	grouping.groups.[groupName].field	4
2.1.5	grouping.groups.[groupName].queries	5

WHAT DOES IT DO?

Solrfluidgrouping can be used to group documents based on a solr field or a set of solr queries.

The following example shows how to group documents based on the “type” field:

```
plugin.tx_solr {
  search {
    grouping = 1
    grouping {
      numberOfGroups = 5
      numberOfResultsPerGroup = 5
      allowGetParameterSwitch = 0
      groups {
        typeGroup {
          field = type
        }
      }
    }
  }
}
```

The next example shows how to group documents based on queries:

```
plugin.tx_solr {
  search {
    grouping = 1
    grouping {
      numberOfGroups = 5
      numberOfResultsPerGroup = 5
      allowGetParameterSwitch = 0
      groups {
        pidQuery {
          queries {
            lessThanTen = pid:[0 TO 10]
            lessThan30 = pid:[11 TO 30]
            rest = pid:[30 TO *]
          }
        }
      }
    }
  }
}
```


CONFIGURATION REFERENCE

2.1 tx_solr.search.grouping

This section defines all available settings for grouping.

- *grouping.numberOfGroups*
- *grouping.numberOfResultsPerGroup*
- *grouping.allowGetParameterSwitch*
- *grouping.groups.[groupName].field*
- *grouping.groups.[groupName].queries*

2.1.1 grouping.numberOfGroups

Type Integer

TS Path plugin.tx_solr.search.grouping.numberOfGroups

Default 5

Since 1.0

2.1.2 grouping.numberOfResultsPerGroup

Type Integer

TS Path plugin.tx_solr.search.grouping.numberOfResultsPerGroup

Default 5

Since 1.0

2.1.3 grouping.allowGetParameterSwitch

Type Boolean

TS Path plugin.tx_solr.search.grouping.allowGetParameterSwitch

Default 0

Since 1.0

2.1.4 grouping.groups.[groupName].field

Type String

TS Path plugin.tx_solr.search.grouping.[groupName].field

Default empty

Since 1.0

Defines the solr field where a group should be build on.

Note: Use either field or queries no mix. Groups with field are field groups, groups with queries are query groups.

2.1.5 grouping.groups.[groupName].queries

Type Array

TS Path plugin.tx_solr.search.grouping.[groupName].queries

Default empty

Since 1.0

Defines an array of queries to group the results in.

Note: Use either field or queries no mix. Groups with field are field groups, groups with queries are query groups.